

PRESTANDADECLARATION / DECLARATION OF PERFORMANCE

i enlighet med / in accordance with EU Construction Products Regulation (CPR) no 305/2011

No. DoP-SE-0243

1. Produkttypens unika identifikationskod / Unique identification code of the product-type:
Weber.tec Dispersionssystem
2. Typ-, parti- eller serienummer eller någon annan beteckning som möjliggör identifiering av byggprodukter i enlighet med artikel 11.4 /
Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):
Batch, produktionsdatum, tillverkningsenhet enligt information på förpackning alt. bifogade dokument. / Batch/production date/production site/serial No. is printed on packaging or accompanying documents
3. Byggproduktens avsedda användning eller användningar i enlighet med den tillämpliga, harmoniserade tekniska specifikationen, såsom förutsett av tillverkaren /
Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Målningsbart tätskiktssystem för golv och väggar / Liquid applied watertight covering kit for floors and walls
4. Tillverkarens namn, registrerade företagsnamn eller registrerade varumärke samt kontaktadress enligt vad som krävs i artikel 11.5 /
Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):
Weber ®
Saint-Gobain Byggprodukter AB
Box 707, Gårdsvägen 18
SE-169 27 SOLNA, Sweden
www.weber.se
5. I tillämpliga fall namn och kontaktadress för tillverkarens representant vars mandat omfattar de uppgifter som anges i artikel 12.2 /
Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
Not applicable
6. Systemet eller systemen för bedömning och fortlöpande kontroll av byggproduktens prestanda enligt bilaga V /
System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
AVCP system 2+
7. För det fall att prestandadeklarationen avser en byggprodukt som omfattas av en harmoniserad standard /
In case of the declaration of performance concerning a construction product covered by a harmonised standard:
Ej tillämpbar / Not applicable
8. För det fall att prestandadeklarationen avser en byggprodukt för vilken en europeisk teknisk bedömning har utfärdats: /
In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
ETA-12/0048 Weber.tec Watertight covering kit
Dancert Danish Technological Institute, notified body No. 1073
utförd/performed **FPC / FPC** under system/under system **2+**
och utfärdad/and issued **1073-CPR-399-01**
enligt / accordance **ETAG 022 watertight covering kits for wet room floors and or walls**

9. Angiven prestanda / Declared performance

Characteristics of product and assessment

ETAG para.	Characteristic	Assessment of characteristic
	2.1 Mechanical resistance and stability	Not relevant.
	2.2 Safety in case of fire	
2.4.1	Reaction to fire	Euroclass F
	2.3 Hygiene, health and the environment	
2.4.2	Dangerous substances	No dangerous materials *)
2.4.3.	Vapour permeability	The sd value of the membrane at RH 100→75 % is 50 m, which is equivalent to $Z_v = 1.800.000$ s/m.
2.4.4	Moisture resistance	
	Water tightness	Watertight according to EN 14891
	Crack bridging ability	Assessment category 1: Crack width 0,4 mm
	Bond strength	Assessment category 2: Bond strength > 0,5 MPa
	Scratching resistance	No performance determined
	Joint bridging ability	Assesment category 2: Watertight
	Water tightness around penetrations	Assesment category 2: Watertight
	2.4 Safety in use	
2.4.5	Slipperiness	Not relevant
	2.5 Protection against noise	Not relevant
	2.6 Energy economy and heat retention	Not relevant
	2.7 Related aspects of durability and serviceability	
2.4.6.1	Resistance to temperature	Assessment category 1: Bond strength > 0,3 MPa
2.4.6.2	Resistance to water	Assessment category 1:

		Bond strength > 0,3 MPa
2.4.6.3	Resistance to alkalinity	Assessment category 1: Bond strength > 0,3 MPa
2.4.6.6	Resistance to mechanical wear	Not relevant
2.4.7.1	Cleanability	Not relevant
2.4.7.2	Repairability	The kit is repairable
2.4.7.3	Thickness	The minimum thickness of the membrane shall be 0,7 mm.
2.4.7.4	Applicability	Applicable

*) In accordance with <http://europa.eu.int/-/comm/enterprise/construction/internal/dangsub/dangmain.htm> In addition to the specific clauses relating to dangerous substances contained in this European Technical Approval, there may be other requirements applicable to the products falling within its scope (e.g. transposed European legislation and national laws, regulations and administrative provisions). In order to meet the provisions of the EU Construction Products Directive, these requirements need also to be complied with, when and where they apply.

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

[Ej tillämpbar/Not applicable](#)

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Tommy Nilsson, SupplyChain manager
(name and function)



Solna den 13-Sep-13
(place and date of issue)

(signature)

Bilagor enligt / Appendices according to regulation Reach (EC) No 1907/2006 Article 31 or Article 33

1. (31) Safety data sheet: [Ej tillämpbart / Not applicable](#)
2. (33) Substances of very high concern: [Ej tillämpbart / Not applicable](#)
3. Övrigt / Other
Valfri / Optional: